



Environmental

Geotechnical

Building Sciences

Construction Quality  
Verification

**Telephone**

(866) 217.7900  
(705) 742.7900

**Facsimile**

(705) 742.7907

**Website**

[cambium-inc.com](http://cambium-inc.com)

**Mailing Address**

P.O. Box 325,  
Peterborough, Ontario  
Canada, K9J 6Z3

**Locations**

Peterborough  
Kingston  
Barrie  
Oshawa

**Laboratory**

Peterborough



December 8, 2023

China Canada Jing Bei Xin Min International Co. Ltd.  
c/o EcoVue Consulting Services Inc.  
311 Goerge Street North,  
Peterborough, ON  
K9J 3H3

Attn: Aditya Srinivas  
Planner

**Re: DRAFT - In-Situ Infiltration Testing – Hidden Ridge Residential  
Development, Uxbridge, Ontario**  
**Cambium Reference: 18619-001**

---

Dear Aditya Srinivas,

China Canada Jing Bei Xin Min International Co. Ltd. (Client), care of EcoVue Consulting Services Inc. (EcoVue) retained Cambium Inc. to complete in-situ infiltration testing at Part Lot 25, Concession 3, Uxbridge Township (the Site).

It is Cambium's understanding that the Site is currently vacant undeveloped land. The Client intends on developing the Site with seven lots, two separate cul-de-sacs, and stormwater management features.

The stormwater management features include ditches along Road A. The ditches will include earthen berms that will impede surface water flow, thereby promoting re-infiltration. The in-situ infiltration testing outlined herein was completed in order to characterize the infiltrative capacity of the soils about 0.3 m below the bottom of the proposed ditches.

As outlined below, the locations and testing depths were approximate and were based off information provided by the Client. Further, testing locations and results were based on surface conditions which influence access of the drilling equipment, and shallow groundwater conditions.



Environmental

Geotechnical

Building Sciences

Construction Quality  
Verification

**Telephone**

(866) 217.7900  
(705) 742.7900

**Facsimile**

(705) 742.7907

**Website**

cambium-inc.com

**Mailing Address**

P.O. Box 325,  
Peterborough, Ontario  
Canada, K9J 6Z3

**Locations**

Peterborough  
Kingston  
Barrie  
Oshawa

**Laboratory**

Peterborough



December 8, 2023

## **Methodology**

### **Infiltration Testing Wells**

Cambium staff were on-site on November 23, 2023 to advance boreholes and install dry wells to facilitate in-situ infiltration testing. The testing locations were determined from hand held GPS devices. The testing depths were inferred from available topographic surface mapping of the Site (as provided by the Client). The locations of the testing wells are outlined on attached Figure 1.

Two dry monitoring wells (labelled IT103-23 and IT104-23) were installed in the southern area of the property (near the southern half of Road A). Specific installation details are included in the attached borehole logs and discussed further below. It is noted that the location of wells IT103-23 and IT104-23 had to be altered from their initial planned locations due to the presence of debris on-site and existing vegetated areas. Borehole logs are attached.

### **Unsuitable Conditions**

Groundwater conditions during the advancement of IT101-23 and IT102-23 were too shallow to allow for installation of a dry testing well at both of these locations. Details regarding the conditions encountered at these locations are discussed in the attached borehole logs, and in the following sections. The locations of boreholes IT101-23 and IT102-23 are outlined on attached Figure 1. Borehole logs are attached.

### **Infiltration Testing Procedures**

Upon completion of IT103-23 and IT104-23 Cambium staff filled each well with potable water to saturate the bentonite seal (overlying the sand pack testing interval).

On November 24, 2023 Cambium staff re-visited the Site to complete testing on wells IT103-23 and IT104-23. The in-situ infiltration testing was completed in general accordance with the procedures outlined in the document titled Time Lag



Environmental

Geotechnical

Building Sciences

Construction Quality  
Verification

**Telephone**

(866) 217.7900

(705) 742.7900

**Facsimile**

(705) 742.7907

**Website**

cambium-inc.com

**Mailing Address**

P.O. Box 325,  
Peterborough, Ontario  
Canada, K9J 6Z3

**Locations**

Peterborough  
Kingston  
Barrie  
Oshawa

**Laboratory**

Peterborough



December 8, 2023

and Soil Permeability In Ground-Water Observations<sup>1</sup>. The data generated from the above testing was processed using the procedures outlined in the above described methodology, and are attached to this document.

## Results

### Water Levels

Groundwater conditions on November 23, 2023 were confirmed by measuring groundwater depths at three existing wells (MW101, MW102 and DW-2). In addition, one borehole (labeled BH105-23) was advanced in the area of IT103-23 to confirm groundwater conditions in that area. The groundwater depths measured on-site were reviewed to ensure there was sufficient separation between the testing interval and groundwater level. The locations of the existing wells, and BH105-23 are outlined on attached Figure 1.

The water levels ranged from 5.26 metres below ground surface (mbgs) to 7.22 mbgs. Groundwater elevations ranged from 244.03 metres above sea level (masl) to 251.24 masl (approximately). Existing well MW101 was measured to be 4.49 m deep, and confirmed to be dry. The water levels measured on-site are outlined in Table 1 below.

**Table 1: Summary of Water Level Measurements (Nov 23, 2023)**

Location	Surface Elevation (masl) <sup>(2)</sup>	Depth (mbgs) <sup>(1)</sup>	Water Level (mbgs) <sup>(1)</sup>	Approximate Groundwater Elevations (masl) <sup>(2)</sup>
MW101 <sup>(3)</sup>	255.10	4.49	Dry	Deeper than 250.61
MW102 <sup>(3)</sup>	256.50	5.50	5.26	251.24
DW-2 <sup>(4)</sup>	251.25	3.36	7.22	244.03
BH105-23 <sup>(5)</sup>	255.20	5.95	4.88	250.32

1. metres below ground surface (existing grade)

2. metres above sea level

3. existing monitoring well

4. existing dug supply well

5. water level measured from borehole advanced on Nov 23, 2023

6. water elevation data based on approximate topographic data provided by the Client

The target testing interval for IT101-23 ranged from approximate elevations of 244.76 masl to 243.26 masl. This testing interval ranged from the bottom of the

<sup>1</sup> Hvorslev, M. (1951), Time Lag and Soil Permeability in Ground-Water Observations, Bulletin No. 36, Waterways Experiment Station USACOE, Vicksburg, Mississippi



Environmental

Geotechnical

Building Sciences

Construction Quality  
Verification

**Telephone**

(866) 217.7900  
(705) 742.7900

**Facsimile**

(705) 742.7907

**Website**

[cambium-inc.com](http://cambium-inc.com)

**Mailing Address**

P.O. Box 325,  
Peterborough, Ontario  
Canada, K9J 6Z3

**Locations**

Peterborough  
Kingston  
Barrie  
Oshawa

**Laboratory**

Peterborough



December 8, 2023

proposed underdrain of the ditch (i.e., 0.3 m below the ditch), to an additional 1.5 m below that depth. These data were referenced from existing topographic mapping provided by the Client. During advancement of IT101-23 the groundwater level was recorded in the borehole at 245.60 masl (i.e., a depth of 1.4 mbgs). As such testing was not possible at this location and the borehole was abandoned.

The target testing interval for IT102-23 ranged from approximate elevations of 248.01 masl to 246.51 masl. This testing interval ranged from the bottom of the proposed underdrain of the ditch (i.e., 0.3 m below the ditch), to an additional 1.5 m below that depth. These data were referenced from existing topographic mapping provided by the Client. This borehole was advanced to 3.05 mbgs. While groundwater was not directly observed within the borehole, saturated soils were observed between depths of approximately 2.75 mbgs and 3.05 mbgs (elevations of 248.00 masl and 247.70 masl). The presence of soil saturation at the target testing depth did not allow for testing to continue at this location. As such testing was not possible at this location and the borehole was abandoned.

**In-situ Testing - IT103-23**

The target testing interval for IW103-23 ranged from approximate elevations of 251.99 masl to 250.49 masl. This testing interval ranged from the bottom of the proposed underdrain of the ditch (i.e., 0.3 m below the ditch), to an additional 1.5 m below that depth. These data were referenced from existing topographic mapping provided by the Client.

The testing interval at IW103-23 ranged from 252.05 masl to 251.34 masl (a testing interval length of 0.71 m). The testing interval could not be advanced further due to termination on a presumed boulder contact. The bottom of the testing interval was 1.02 m above the water elevation reported at BH105-23, as such the testing is considered valid. The soils encountered throughout the testing interval were described as a sandy silt till, some gravel. Some sand lenses were noted. The hydraulic conductivity of the test interval soils ranged from  $6.51 \times 10^{-6}$  m/sec to  $7.28 \times 10^{-6}$  m/sec. The hydraulic conductivity results were converted to an infiltration rate referencing the methods outlined by the Ontario Ministry of



Environmental

Geotechnical

Building Sciences

Construction Quality  
Verification

**Telephone**

(866) 217.7900  
(705) 742.7900

**Facsimile**

(705) 742.7907

**Website**

[cambium-inc.com](http://cambium-inc.com)

**Mailing Address**

P.O. Box 325,  
Peterborough, Ontario  
Canada, K9J 6Z3

**Locations**

Peterborough  
Kingston  
Barrie  
Oshawa

**Laboratory**

Peterborough



December 8, 2023

Municipal Affairs and Housing<sup>2</sup>. The infiltration rate of the screened soils ranged from 76 mm/hr to 78 mm/hr (geometric mean of 77 mm/hr). The Low Impact Development Design Guide<sup>3</sup> indicates that a safety correction factor should be applied to the tested infiltration rate for design purposes. A safety correction factor of 2.5 was applied to the geometric mean infiltration rate. The infiltration rate of the testing interval at well IW101-23, including safety correction factor, was calculated to be 31 mm/hr (i.e., 77 mm/hr / 2.5 = 31 mm/hr). These results are outlined in Table 2.

**In-Situ Testing - IT104-23**

The target testing interval for IT104-23 ranged from approximate elevations of 252.80 masl to 251.30 masl. This testing interval ranged from the bottom of the underdrain of the ditch (i.e., 0.3 m below the ditch), to an additional 1.5 m below that depth. These data were referenced from existing topographic mapping provided by the Client.

The testing interval at IW104-23 ranged from 252.80 masl to 252.15 masl (a testing interval length of 0.35 m). The bottom of the testing interval was 1.83 m above the water elevation reported at MW102, as such the testing is considered valid.

The soils encountered throughout the testing interval were described as silty sand, trace clay. The hydraulic conductivity of the test interval soils ranged from  $1.90 \times 10^{-6}$  m/sec to  $2.50 \times 10^{-6}$  m/sec. The hydraulic conductivity results were converted to an infiltration rate referencing the methods outlined by the Ontario Ministry of Municipal Affairs and Housing. The infiltration rate of the screened soils ranged from 55 mm/hr to 59 mm/hr (geometric mean of 57 mm/hr). The Low Impact Development Design Guide indicates that a safety correction factor should be applied to the tested infiltration rate for design purposes. A safety correction factor of 2.5 was applied to the geometric mean infiltration rate. The

---

<sup>2</sup> Ontario Ministry of Municipal Affairs and Housing. (1997), Supplementary Guidelines to the Ontario Building Code 1997. SG-6 Percolation Time and Soil Descriptions. Toronto, Ontario.

<sup>3</sup> Toronto and Region Conservation Authority. (2010), Low Impact Development Stormwater Management Planning and Design Guide.



Environmental

Geotechnical

Building Sciences

Construction Quality Verification

**Telephone**  
(866) 217.7900  
(705) 742.7900

**Facsimile**  
(705) 742.7907

**Website**  
cambium-inc.com

**Mailing Address**  
P.O. Box 325,  
Peterborough, Ontario  
Canada, K9J 6Z3

**Locations**  
Peterborough  
Kingston  
Barrie  
Oshawa

**Laboratory**  
Peterborough



December 8, 2023

infiltration rate of the testing interval at well IT104-23, including safety correction factor, was calculated to be 23 mm/hr (i.e., 57 mm/hr / 2.5 = 23 mm/hr). These results are outlined in Table 2.

Summary of In-Situ Testing Results

The details regarding the in-situ infiltration testing are outlined below in Table 2.

**Table 2: Summary of In-situ Testing Results (Nov 23, 2023)**

Location	Testing Interval/ Elevation (masl <sup>1</sup> )	Testing Interval/ Depth (mbgs <sup>2</sup> )	Test #	Hydraulic Conductivity (m/sec)	Infiltration Rate (mm/hr)	Geometric Mean Infiltration Rate (mm/hr)	Geometric Mean Infiltration Rate (mm/hr) – Including Safety Correction Factor
IT103-23	252.05 to 251.34	2.95 to 3.66	1	6.52 x 10 <sup>-6</sup>	76	77	31
			2	7.28 x 10 <sup>-6</sup>	78		
			3	6.51 x 10 <sup>-6</sup>	76		
IT104-23	252.05 to 251.34	2.95 to 3.66	1	1.90 x 10 <sup>-6</sup>	55	57	23
			2	2.50 x 10 <sup>-6</sup>	59		

1. metres above sea level
2. metres below ground surface (existing grade)

**Closing**

The results indicate that in the southern area of the proposed infiltration features (in the area of IT103-23 and IT104-23), at the tested intervals, the infiltration rate ranged between 23 mm/hr and 31 mm/hr (including the safety correction factor). In-situ testing could be completed further north at locations IT101-23 and IT102-23 due to the presence of a shallow water table.

We trust the information outlined herein is sufficient. Please reach out to the undersigned at 1705-742-7900 if you have any questions.



Environmental

Geotechnical

Building Sciences

Construction Quality  
Verification

**Telephone**

(866) 217.7900  
(705) 742.7900

**Facsimile**

(705) 742.7907

**Website**

[cambium-inc.com](http://cambium-inc.com)

**Mailing Address**

P.O. Box 325,  
Peterborough, Ontario  
Canada, K9J 6Z3

**Locations**

Peterborough  
Kingston  
Barrie  
Oshawa

**Laboratory**

Peterborough



December 8, 2023

Best regards,

**Cambium Inc.**

---

**Cameron MacDougall, P.Geo.**  
**Project Manager**

*CJM*

*Encl.     Figure 1. Site Plan  
             Borehole Logs  
             Infiltration Testing Data*

*P:\18600 to 18699\18619-001 EcoVue - GEO - Investigation of SWM Features for Hidden Ridge Dev\Deliverables\REPORT - LTR Infiltration RPT\Draft\2023-12-04 Infiltration RPT.docx*





# **IN-SITU INFILTRATION TESTING** CHINA CANADA JING BEI XIN MIN INTERNATIONAL CO. LTD. Part Lot 25, Concession 3 Uxbridge, Ontario

## **LEGEND**

-  Borehole (Cambium, 2023)
-  Existing Well
-  Infiltration Well
-  Dug Supply Well
-  Site (approximate)

**Notes:**  
 - This document contains information licensed under the Open Government License - Ontario.  
 - Distances on this plan are in metres and can be converted to feet by dividing by 0.3048.  
 - Cambium Inc. makes every effort to ensure this map is free from errors but cannot be held responsible for any damages due to error or omissions. This map should not be used for navigation or legal purposes. It is intended for general reference use only.



194 Sophia Street  
 Peterborough, Ontario, K9H 1E5  
 Tel: (705) 742.7900 Fax: (705) 742.7907  
 www.cambium-inc.com

## **SITE PLAN**

Project No.:	18619-001	Date:	December 2023
Scale:	1:1,250	Rev.:	
Created by:	DBB	Projection:	NAD 1983 UTM Zone 17N
Checked by:	CM	Figure:	<b>1</b>





In-Situ Borehole Infiltration Testing Calculator

Location: IT103-23

Date: Nov 24, 2023

Test 1

Input Data

ASSUME m (transformation ratio) = 1

L	Length of Intake Sample	cm	71
D	Diameter of Intake Sample	cm	11.4
d	Diameter of Standpipe	cm	5

H1	Initial Head		cm	57.71
H2	End Head		cm	1
T1	Initial Time		sec	0
T2	End Time		sec	690

mL 71

mL/D 6.22807

RESULT

kh	6.52E-04	cm/sec
kh	6.52E-06	m/sec

Equation:

Scenario G - Variable Head

$$k_h = \frac{d^2 \cdot \ln \left[ \frac{mL}{D} + \sqrt{1 + \left( \frac{mL}{D} \right)^2} \right]}{8 \cdot L \cdot (t_2 - t_1)} \ln \frac{H_1}{H_2}$$

$$k_h = \frac{d^2 \cdot \ln \left( \frac{2mL}{D} \right)}{8 \cdot L \cdot (t_2 - t_1)} \ln \frac{H_1}{H_2} \text{ FOR } \frac{mL}{D} > 4$$

Citation: Hvorslev, M. (1951) Time Lag and Soil Permeability in Ground-Water Observations, Bulletin No. 36, Waterways Experiment Station USACOE, Vicksburg, Mississippi

Infiltration Rate Estimation (no safety correction factor applied)	76 mm/hr
--	----------

Citation: Ontario Ministry of Municipal Affairs and Housing (OMMAH). 1997. Supplementary Guidelines to the Ontario Building Code 1997. SG-6 Percolation Time and Soil Descriptions.



In-Situ Borehole Infiltration Testing Calculator

Location: IT103-23

Date: Nov 24, 2023

Test 2

Input Data

ASSUME m (transformation ratio) = 1

L	Length of Intake Sample	cm	71
D	Diameter of Intake Sample	cm	11.4
d	Diameter of Standpipe	cm	5

H1	Initial Head		cm	42.11
H2	End Head		cm	1
T1	Initial Time		sec	0
T2	End Time		sec	570

mL 71

mL/D 6.22807

RESULT

kh	7.28E-04	cm/sec
kh	7.28E-06	m/sec

Equation:

Scenario G - Variable Head

$$k_h = \frac{d^2 \cdot \ln \left[ \frac{mL}{D} + \sqrt{1 + \left( \frac{mL}{D} \right)^2} \right]}{8 \cdot L \cdot (t_2 - t_1)} \ln \frac{H_1}{H_2}$$

$$k_h = \frac{d^2 \cdot \ln \left( \frac{2mL}{D} \right)}{8 \cdot L \cdot (t_2 - t_1)} \ln \frac{H_1}{H_2} \text{ FOR } \frac{mL}{D} > 4$$

Citation: Hvorslev, M. (1951) Time Lag and Soil Permeability in Ground-Water Observations, Bulletin No. 36, Waterways Experiment Station USACOE, Vicksburg, Mississippi

Infiltration Rate Estimation (no safety correction factor applied)	78 mm/hr
--	----------

Citation: Ontario Ministry of Municipal Affairs and Housing (OMMAH). 1997. Supplementary Guidelines to the Ontario Building Code 1997. SG-6 Percolation Time and Soil Descriptions.



# In-Situ Borehole Infiltration Testing Calculator

Location: IT103-23

Date: Nov 24, 2023

Test **3**

## Input Data

ASSUME m (transformation ratio) = 1

L	Length of Intake Sample	cm	71
D	Diameter of Intake Sample	cm	11.4
d	Diameter of Standpipe	cm	5

H1	Initial Head		cm	40.12
H2	End Head		cm	1
T1	Initial Time		sec	0
T2	End Time		sec	630

mL 71

mL/D 6.22807

## RESULT

kh	6.51E-04	cm/sec
kh	6.51E-06	m/sec

Equation:

Scenario G - Variable Head

$$k_h = \frac{d^2 \cdot \ln \left[ \frac{mL}{D} + \sqrt{1 + \left( \frac{mL}{D} \right)^2} \right]}{8 \cdot L \cdot (t_2 - t_1)} \ln \frac{H_1}{H_2}$$

$$k_h = \frac{d^2 \cdot \ln \left( \frac{2mL}{D} \right)}{8 \cdot L \cdot (t_2 - t_1)} \ln \frac{H_1}{H_2} \text{ FOR } \frac{mL}{D} > 4$$

Citation: Hvorslev, M. (1951) Time Lag and Soil Permeability in Ground-Water Observations, Bulletin No. 36, Waterways Experiment Station USACOE, Vicksburg, Mississippi

Infiltration Rate Estimation (no safety correction factor applied)	76 mm/hr
--	----------

Citation: Ontario Ministry of Municipal Affairs and Housing (OMMAH). 1997. Supplementary Guidelines to the Ontario Building Code 1997. SG-6 Percolation Time and Soil Descriptions.



# In-Situ Borehole Infiltration Testing Calculator

Location: IT104-23

Date: Nov 24, 2023

Test 1

## Input Data

ASSUME m (transformation ratio) = 1

L	Length of Intake Sample	cm	65
D	Diameter of Intake Sample	cm	11.4
d	Diameter of Standpipe	cm	5

H1	Initial Head		cm	39.51
H2	End Head		cm	1
T1	Initial Time		sec	0
T2	End Time		sec	2265

mL 65

mL/D 5.701754

## RESULT

kh	1.90E-04	cm/sec
kh	1.90E-06	m/sec

Equation:

Scenario G - Variable Head

$$k_h = \frac{d^2 \cdot \ln \left[ \frac{mL}{D} + \sqrt{1 + \left( \frac{mL}{D} \right)^2} \right]}{8 \cdot L \cdot (t_2 - t_1)} \ln \frac{H_1}{H_2}$$

$$k_h = \frac{d^2 \cdot \ln \left( \frac{2mL}{D} \right)}{8 \cdot L \cdot (t_2 - t_1)} \ln \frac{H_1}{H_2} \text{ FOR } \frac{mL}{D} > 4$$

Citation: Hvorslev, M. (1951) Time Lag and Soil Permeability in Ground-Water Observations, Bulletin No. 36, Waterways Experiment Station USACOE, Vicksburg, Mississippi

Infiltration Rate Estimation (no safety correction factor applied) 55 mm/hr

Citation: Ontario Ministry of Municipal Affairs and Housing (OMMAH). 1997. Supplementary Guidelines to the Ontario Building Code 1997. SG-6 Percolation Time and Soil Descriptions.





In-Situ Borehole Infiltration Testing Calculator

Location: IT104-23

Date: Nov 24, 2023

Test 1

Input Data

ASSUME m (transformation ratio) = 1

L	Length of Intake Sample	cm	65
D	Diameter of Intake Sample	cm	11.4
d	Diameter of Standpipe	cm	5

H1	Initial Head		cm	24.78
H2	End Head		cm	1
T1	Initial Time		sec	0
T2	End Time		sec	1500

mL 65

mL/D 5.701754

RESULT

kh	2.50E-04	cm/sec
kh	2.50E-06	m/sec

Equation:

Scenario G - Variable Head

$$k_h = \frac{d^2 \cdot \ln \left[ \frac{mL}{D} + \sqrt{1 + \left( \frac{mL}{D} \right)^2} \right]}{8 \cdot L \cdot (t_2 - t_1)} \ln \frac{H_1}{H_2}$$

$$k_h = \frac{d^2 \cdot \ln \left( \frac{2mL}{D} \right)}{8 \cdot L \cdot (t_2 - t_1)} \ln \frac{H_1}{H_2} \text{ FOR } \frac{mL}{D} > 4$$

Citation: Hvorslev, M. (1951) Time Lag and Soil Permeability in Ground-Water Observations, Bulletin No. 36, Waterways Experiment Station USACOE, Vicksburg, Mississippi

Infiltration Rate Estimation (no safety correction factor applied)	59 mm/hr
--	----------

Citation: Ontario Ministry of Municipal Affairs and Housing (OMMAH). 1997. Supplementary Guidelines to the Ontario Building Code 1997. SG-6 Percolation Time and Soil Descriptions.



China Canada Jing Bei  
Xin Min Intl c/o EcoVue  
Consulting Services

**Client:**  
**Contractor:** Drilltech  
**Project No.:** 18619-001  
**Location:** Ontario, Canada

**Project Name:** In-Situ Infiltration Testing, Hidden Ridge  
**Method:** Truck Mounted Solid Stem Auger  
**Elevation:** 247 mASL  
**UTM:** 17T **N:** 4895706.3 **E:** 638831.1

**Log of Borehole:** IT101-23  
**Page:** 1 of 1  
**Date Completed:** Nov 23, 2023

SUBSURFACE PROFILE					SAMPLE													
Elevation (m)	Depth	Lithology	Description	Elevation Depth	Number	Type	% Recovery	SPT (N)	Atterberg Limits (%)			Shear Strength Cu, kPa			Well Installation	Log Notes		
									LL	PL	PI	nat V. rem V.	20	40			60	80
25	50	75	% Moisture	25	50	75	SPT (N)	20	40	60	80							
25	50	75	20	40	60	80												
247	0	<div><div></div><div></div><div></div><div></div></div> <div>(ML) SILT and SAND: SILT and SAND, some gravel, brown, saturated.</div>													Groundwater measured at 1.4 mbgs on completion.			
246.5	0.5																	
246	1																	
245.5	1.5		1	GB														
245	2																	
244.5	2.5																	
244	3		243.95													Borehole caved at 2.6 mbgs on completion.		
243.5	3.5		3.05															
243	4																	
242.5	4.5																	
242	5																	
241.5	5.5																	
241	6																	
240.5	6.5																	
240	7																	
239.5																		
GRAINSIZE DISTRIBUTION																		
SAMPLE GRAVEL SAND SILT CLAY																		

1m = 24 units







China Canada Jing Bei  
Xin Min Intl c/o EcoVue  
Consulting Services

**Client:**  
**Contractor:** Drilltech  
**Project No.:** 18619-001  
**Location:** Ontario, Canada

**Project Name:** In-Situ Infiltration Testing, Hidden Ridge  
**Method:** Truck Mounted Solid Stem Auger  
**Elevation:** 250.75 mASL  
**UTM:** 17T **N:** 4895661.6 **E:** 638844.8

**Log of Borehole:** IT102-23  
**Page:** 1 of 1  
**Date Completed:** Nov 23, 2023

SUBSURFACE PROFILE					SAMPLE													
Elevation (m)	Depth	Lithology	Description	Elevation Depth	Number	Type	% Recovery	SPT (N)	Atterberg Limits (%)			Shear Strength Cu, kPa			Well Installation	Log Notes		
									LL	PL	PI	nat V. rem V.	20	40				
														25			50	75
									% Moisture			SPT (N)						
									25 50 75			20 40 60 80						
250.8	0		TOPSOIL: TOPSOIL	250.52	1A	SS												
			FILL: SAND FILL, medium grained, brown, moist	0.23	1B	SS	100	4										
250.2	0.5			249.99														
			(ML) CLAYEY SILT: CLAYEY SILT, brown, dryer than plastic limit to about plastic limit	0.76														
249.8	1																	
249.2	1.5				2A	SS												
				248.87			100	16										
248.8	2		(SW) gravelly SAND: gravelly SAND TILL, some silt, some clay,	1.88	2B	SS												
248.2	2.5		becomes trace silt															
			Becomes wet, becomes coarse sand		3	SS	100	33										
247.8	3			247.7														
			Borehole terminated @ 3 mbgs due to target depth achieved.	3.05														
247.2	3.5																	
246.8	4																	
246.2	4.5																	
245.8	5																	
245.2	5.5																	
244.8	6																	
244.2	6.5																	
243.8	7																	
243.2																		
GRAINSIZE DISTRIBUTION																		
SAMPLE GRAVEL SAND SILT CLAY																		

Borehole caved at 2.87 mbgs and was dry on completion. Groundwater encountered in SPT sample @ 2.90 mbgs.

1m = 24 units

Borehole caved at  
2.87 mbgs and was  
dry on completion.  
Groundwater  
encountered in SPT  
sample @ 2.90 mbgs.

Logged By: TP

Input By: TP

Peterborough, Barrie, Oshawa, Kingston, Ottawa




China Canada Jing Bei  
Xin Min Intl c/o EcoVue  
Consulting Services

**Client:**  
**Contractor:** Drilltech  
**Project No.:** 18619-001  
**Location:** Ontario, Canada

**Project Name:** In-Situ Infiltration Testing, Hidden Ridge  
**Method:** Truck Mounted Solid Stem Auger  
**Elevation:** 255 mASL  
**UTM:** 17T **N:** 4895584 **E:** 638852

**Log of Borehole:** IT103-23  
**Page:** 1 of 1  
**Date Completed:** Nov 23, 2023



Logged By: TP

Input By: TP

Peterborough, Barrie, Oshawa, Kingston, Ottawa






China Canada Jing Bei  
Xin Min Intl c/o EcoVue  
Consulting Services

**Client:**  
**Contractor:** Drilltech  
**Project No.:** 18619-001  
**Location:** Ontario, Canada

**Project Name:** In-Situ Infiltration Testing, Hidden Ridge  
**Method:** Truck Mounted Solid Stem Auger  
**Elevation:** 255.75 mASL  
**UTM:** 17T **N:** 4895557 **E:** 638875

**Log of Borehole:** IT104-23  
**Page:** 1 of 1  
**Date Completed:** Nov 23, 2023



Logged By: TP

Input By: TP

Peterborough, Barrie, Oshawa, Kingston, Ottawa



China Canada Jing Bei  
Xin Min Intl c/o EcoVue  
Consulting Services

**Client:**  
**Contractor:** Drilltech  
**Project No.:** 18619-001  
**Location:** Ontario, Canada

**Project Name:** In-Situ Infiltration Testing, Hidden Ridge  
**Method:** Truck Mounted Solid Stem Auger  
**Elevation:** 255.2 mASL  
**UTM:** 17T **N:** 4895586 **E:** 638869

**Log of Borehole:** BH105-23  
**Page:** 1 of 1  
**Date Completed:** Nov 23, 2023

SUBSURFACE PROFILE				SAMPLE														
Elevation (m)	Depth	Lithology	Description	Elevation Depth	Number	Type	% Recovery	SPT (N)	Atterberg Limits (%)			Shear Strength Cu, kPa			Well Installation	Log Notes		
									LL	PL	PI	nat V. rem V.	20	40			60	80



Environmental

Geotechnical

Building Sciences

Construction Quality  
Verification

**Telephone**

(866) 217.7900

(705) 742.7900

**Facsimile**

(705) 742.7907

**Website**

cambium-inc.com

**Mailing Address**

P.O. Box 325,  
Peterborough, Ontario  
Canada, K9J 6Z3

**Locations**

Peterborough  
Kingston  
Barrie  
Oshawa

**Laboratory**

Peterborough



December 8, 2023

## CAMBIUM QUALIFICATIONS AND LIMITATIONS

### Limited Warranty

In performing work on behalf of a client, Cambium relies on its client to provide instructions on the scope of its retainer and, on that basis, Cambium determines the precise nature of the work to be performed. Cambium undertakes all work in accordance with applicable accepted industry practices and standards. Unless required under local laws, other than as expressly stated herein, no other warranties or conditions, either expressed or implied, are made regarding the services, work or reports provided.

### Reliance on Materials and Information

The findings and results presented in reports prepared by Cambium are based on the materials and information provided by the client to Cambium and on the facts, conditions and circumstances encountered by Cambium during the performance of the work requested by the client. In formulating its findings and results into a report, Cambium assumes that the information and materials provided by the client or obtained by Cambium from the client or otherwise are factual, accurate and represent a true depiction of the circumstances that exist. Cambium relies on its client to inform Cambium if there are changes to any such information and materials. Cambium does not review, analyze or attempt to verify the accuracy or completeness of the information or materials provided, or circumstances encountered, other than in accordance with applicable accepted industry practice. Cambium will not be responsible for matters arising from incomplete, incorrect or misleading information or from facts or circumstances that are not fully disclosed to or that are concealed from Cambium during the provision of services, work or reports.

Facts, conditions, information and circumstances may vary with time and locations and Cambium's work is based on a review of such matters as they existed at the particular time and location indicated in its reports. No assurance is made by Cambium that the facts, conditions, information, circumstances or any underlying assumptions made by Cambium in connection with the work performed will not change after the work is completed and a report is submitted. If any such changes occur or additional information is obtained, Cambium should be advised and requested to consider if the changes or additional information affect its findings or results.

When preparing reports, Cambium considers applicable legislation, regulations, governmental guidelines and policies to the extent they are within its knowledge, but Cambium is not qualified to advise with respect to legal matters. The presentation of information regarding applicable legislation, regulations, governmental guidelines and policies is for information only and is not intended to and should not be interpreted as constituting a legal opinion concerning the work completed or conditions outlined in a report. All legal matters should be reviewed and considered by an appropriately qualified legal practitioner.

### Site Assessments

A site assessment is created using data and information collected during the investigation of a site and based on conditions encountered at the time and particular locations at which fieldwork is conducted. The information, sample results and data collected represent the conditions only at the specific times at which and at those specific locations from which the information, samples and data were obtained and the information, sample results and data may vary at other locations and times. To the extent that Cambium's work or report considers any locations or times other than those from which information, sample results and data was specifically received, the work or report is based on a reasonable extrapolation from such information, sample results and data but the actual conditions encountered may vary from those extrapolations.

Only conditions at the site and locations chosen for study by the client are evaluated; no adjacent or other properties are evaluated unless specifically requested by the client. Any physical or other aspects of the site chosen for study by the client, or any other matter not specifically addressed in a report prepared by Cambium, are beyond the scope of the work performed by Cambium and such matters have not been investigated or addressed.

### Reliance

Cambium's services, work and reports may be relied on by the client and its corporate directors and officers, employees, and professional advisors. Cambium is not responsible for the use of its work or reports by any other party, or for the reliance on, or for any decision which is made by any party using the services or work performed by or a report prepared by Cambium without Cambium's express written consent. Any party that relies on services or work performed by Cambium or a report prepared by Cambium without Cambium's express written consent, does so at its own risk. No report of Cambium may be disclosed or referred to in any public document without Cambium's express prior written consent. Cambium specifically disclaims any liability or responsibility to any such party for any loss, damage, expense, fine, penalty or other such thing which may arise or result from the use of any information, recommendation or other matter arising from the services, work or reports provided by Cambium.

### Limitation of Liability

Potential liability to the client arising out of the report is limited to the amount of Cambium's professional liability insurance coverage. Cambium shall only be liable for direct damages to the extent caused by Cambium's negligence and/or breach of contract. Cambium shall not be liable for consequential damages.

### Personal Liability

The client expressly agrees that Cambium employees shall have no personal liability to the client with respect to a claim, whether in contract, tort and/or other cause of action in law. Furthermore, the client agrees that it will bring no proceedings nor take any action in any court of law against Cambium employees in their personal capacity.