



NOTES:

1. SERVICE TO EXTEND 1.5M INSIDE PROPERTY LINE.
2. UNDER NO CIRCUMSTANCE SHALL SERVICES CROSS ONE ANOTHER.
3. EACH HOUSE MAY BE SUPPLIED WITH A SEPARATE 100MM SANITARY SEWER SERVICE LATERAL. COMMON SERVICE CONNECTIONS WITH Y'S WILL NOT BE PERMITTED.
4. THE MINIMUM SIZE FOR STORM DRAIN CONNECTION SHALL BE 100MM INSTALLLED AT A MINIMUM GRADE OF 2% FROM THE STORM SEWER TO THE BUILDING ENVELOPE.
5. THE MINIMUM SIZE FOR SANITARY LATERALS SHALL BE 100MM INSTALLLED AT A MINIMUM GRADE OF 2% FROM THE SANITARY SEWER TO THE BUILDING ENVELOPE.
6. ALL UNDERGROUND SERVICE CABLES TO BE PLACED MINIMUM 1.0m BELOW FINISHED GRADE OF LOTS.
7. SHUT-OFF VALVES TO BE PLACED ON PROPERTY LINE.
8. ALL DIMENSION IN METRES.

APPROVED	TOWNSHIP OF UXBRIDGE	DATE OF ISSUE MARCH, 1989
REVISION 2	SERVICE LOCATION SEMI DETACHED RESIDENTIAL	DRAWING NO. US - 162
DATE OF REVISION MAY, 2005		