



NOTES

- 1 DIMENSIONS FOR BURIED PORTION OF POSTS ARE MINIMUM
- 2 TOPS OF WOODEN POSTS TO BE SAWN OFF WITH 5mm PITCH HIGH SIDE TO BE NEXT TO THE WIRE & 50mm ABOVE IT.
- 3 LENGTH OF POSTS: LINE POSTS 2.45 m MIN., END, CORNER, ANCHOR AND GATE POSTS 2.65 m MIN.
- 4 ALL STAPLES 45 mm, ALL WIRE 17 9 GAUGE.
5. DIMENSIONS IN mm EXCEPT AS NOTED.
- 6 ALL POST TO BE 150 mm MIN DIA. CEDAR UNLESS OTHERWISE NOTED

9 WIRES UNEVENLY SPACED	203	152	254	7 WIRES UNEVENLY SPACED
9 WIRES EVENLY SPACED	203	152	229	9 WIRES EVENLY SPACED
9 WIRES UNEVENLY SPACED	203	152	203	9 WIRES UNEVENLY SPACED
9 WIRES UNEVENLY SPACED	178	152	203	9 WIRES UNEVENLY SPACED
9 WIRES UNEVENLY SPACED	152	152	178	9 WIRES UNEVENLY SPACED
9 WIRES UNEVENLY SPACED	127	152	152	9 WIRES UNEVENLY SPACED
9 WIRES UNEVENLY SPACED	100	152	152	9 WIRES UNEVENLY SPACED
9 WIRES UNEVENLY SPACED	100	152	152	9 WIRES UNEVENLY SPACED
9 WIRES UNEVENLY SPACED	100	152	152	9 WIRES UNEVENLY SPACED
9 WIRES UNEVENLY SPACED	100	152	152	9 WIRES UNEVENLY SPACED

WIRE SPACING

APPROVED	TOWNSHIP OF UXBRIDGE	DATE OF ISSUE MARCH, 1981
REVISION	STANDARD FARM FENCE	DRAWING No. US-312
DATE OF REVISION		